

LifeKit by MTTS



COLIBRI

An **LED phototherapy** device for effective treatment of **neonatal jaundice** with optional 2-hour battery back up



Overview

- user selectable "standard" and "intensive" modes
- used with premature and full term neonates
- compatible with any radiant warmer, infant bed or incubator available on the market
- no moving parts, no internal fans

LED Lights

- optimal light spectrum for treatment of jaundice
- height adjustment maximizes skin surface area exposure

Power Supply

- medical-grade power supply
- 3 prong connection for safe electric grounding (Class I)
- fuse for electrical protection
- optional 2h battery back up

Controls

- on/off button
- control button to toggle between normal and intensive mode

Displays/Indicators

- bright, 'across the room' readable LED display
- treatment time counter
- total system time counter (lifetime)
- total intensive mode system time counter (lifetime)
- standard/intensive mode indicator

Stand

- adjustable height (115-140cm from the light source) to suit different bed heights
- durable caster wheels with locks



Dimensions and Weight

Unit dimensions (max height) 60 cm x 55 cm x 155 cm Shipping (boxed) dimensions 26 cm x 65 cm x 108 cm

Height Adjustment25 cmNet Weight16.0 kgShipping Weight23.5 kg

Performance Specifications

Peak wavelength445 to 465 nmLight Spectrum Peak455 nmLamp duration60,000 hoursEffective surface area50 cm x 30 cm

Total spectral irradiance Standard mode: 37.0 µW.cm⁻².nm⁻¹

Intensive mode: $53.0 \mu W.cm^{-2}.nm^{-1}$

Relative local distribution Standard mode: 0.59 (IEC compliant --> 0.4)

Intensive mode: 0.60 (IEC compliant --> 0.4)


Requirements

Power characteristics 60W, 100-240VAC, 47-63Hz

Agency Requirements ISO 13485: 2016

EN 60601-1:2006/AC2010 EN IEC 60601-2-50: 2003

Colibri unique angled design feature ensures maximum skin coverage



Ordering Information and Servicing

MAIN UNIT ITEM ORDER NO

Colibri PT Unit CL1-1000 Main Unit

ACCESSORIES ITEM ORDER NO

Eye Patch YPT-1013 Size: adjustable
Battery Back up CL1-1020 Internal - 2h
Lightmeter LM-800

User Manual CL1-1031/2/3/4/5 EN, VN, FR, SP, RU

WARRANTY

Standard Warranty 1 year Subject to MTTS policy



MEDICAL TECHNOLOGY TRANSFER AND SERVICES Co., LTD ISO 13485: 2016 Certified Company

For more information or to place an order please contact us at:

@ info@mtts-asia.com

http://mtts-asia.com

666 521

No 26, Lane 41 An Duong Vuong Street Phu Thuong Ward, Tay Ho District Hanoi, Vietnam

Distributor: